








Slagleklipper med hydraulisk sideforskydning

Model					Trepunktsfæste		Højde til liftarm	Min. afstand liftarme		
	Bredde cm	Antal slagler	Antal remme	AxBxC cm		Sideforskudt cm	cm	cm	hk	kg
HNEFGCH125	122	20	3	79x140x90	Hydraulisk sideforskydelig	60/65	28	67	18-25	287
HNEFGCH145	150	24	3	79x170x90	Hydraulisk sideforskydelig	60/90	28	67	30-50	352
HNEFGCH175	175	28	3	79x190x90	Hydraulisk sideforskydelig	60/115	28	67	40-50	397
HNEFGCH200	200	32	4	79x218x90	Hydraulisk sideforskydelig	80/120	28	77	55-70	430
HNEFGCH220	220	36	4	79x238x90	Hydraulisk sideforskydelig	80/140	28	77	75-90	470
MATGK200S	200	26	4	102x220x89	Hydraulisk sideforskydelig	84/118	35	76	50-75	565
MATGK220S	220	28	4	102x240x89	Hydraulisk sideforskydelig	84/138	35	76	60-95	585
MATGKHS240	240	20	5	118x264x120	Hydraulisk sideforskydelig	108/130	35	80	70-90	770
MATGKHS260	260	22	5	118x284x120	Hydraulisk sideforskydelig	108/150	35	80	70-90	804
MATGKHS290	290	24	5	118x314x120	Hydraulisk sideforskydelig	108/180	35	80	70-90	854
HNAG170	170	16	3	98x185x98	Hydraulisk sideforskydelig	56/114	35	67	55-70	438
HNAG220	220	20	4	98x235x98	Hydraulisk sideforskydelig	100/140	35	85	55-90	648
SAVCDH260	250	22	4	117x280x118	Hydraulisk sideforskydelig	105/150	35	90	83-130	1053
SAVCDH300	300	26	5	117x320x118	Hydraulisk sideforskydelig	105/190	35	90	100-130	1173

DK·TEC